

523, 386

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/015697 A1

(51) International Patent Classification⁷: **G11B 7/005,**
20/10

(21) International Application Number:
PCT/IB2003/003288

(22) International Filing Date: 21 July 2003 (21.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02078240.5 6 August 2002 (06.08.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **VOORMAN, Johannes, O.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656

AA Eindhoven (NL). **DE JONG, Gerben, W.** [NL/NL];
c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
BREKELMANS, Johannes, H., A. [NL/NL]; c/o Prof.
Holstlaan 6, NL-5656 AA Eindhoven (NL).



(74) Agent: **DUIJVESTIJN, Adrianus, J.**; Philips Intellectual
Property & Standards, Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: OPTICAL DISK SYSTEM WITH NON-LINEARLY CONTROLLED AMPLIFIER



(57) **Abstract:** Optical disk systems comprising photo detectors (1) with variable gain amplifiers (10) and slicers (11) are provided with generators (12) in feedback paths between slicer (11) and amplifier (10) for controlling said amplifier (10) non-linearly. As a result, time constants of the control loop of said amplifier (10) which depend upon the level of the input signals are now compensated and the timing behavior of the control loop of said amplifier (10) has got a more continuous character. Said generator (12) comprises a converter (13) and is of low complexity and easy to integrate on a photo detector integrated-circuit together with said amplifier (10) and slicer (11) followed by a differential time delay detector (6). Said generator (12) comprises a further converter (14) with a capacitor (15) forming an integrator for making the mean value of the output voltage signal of said slicer (11) equal to zero.

WO 2004/015697 A1